

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 March 2005 (17.03.2005)


PCT

(10) International Publication Number
WO 2005/024932 A3

- (51) International Patent Classification⁷: **H01L 21/68**, 21/52, 21/78, B23Q 11/00, B23D 59/00, H05K 13/04
- (21) International Application Number: PCT/JP2004/013281
- (22) International Filing Date: 7 September 2004 (07.09.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2003-315269 8 September 2003 (08.09.2003) JP
- (71) Applicant (for all designated States except US): MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 5718501 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KABESHITA, Akira. HAMASAKI, Kurayasu. MINAMITANI, Shozo. MAKINO, Yoichi. TANI, Noriyuki.
- (74) Agents: KAWAMIYA, Osamu et al.; Aoyama & Partners, IMP Building, 3-7, Shiromi 1-chome, Chuo-ku, Osaka-shi, Osaka 5400001 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR REMOVING SEMICONDUCTOR CHIP



(57) Abstract: While a vicinity of a bottom surface-side region of a pressure-sensitive adhesive sheet (3) corresponding to an adhesion region (R1) of a semiconductor chip (1) are sucked and held, a plurality of protruding portions (30) of a removing member (21) are brought into contact with the bottom surface of the semiconductor chip through the adhesive sheet at the region. Also, the adhesive sheet is sucked in between the respective protruding portions so as to change a surface bonding of the semiconductor chip to the adhesive sheet by adhesion to a point bonding, and further the removing member is moved along the bottom surface of the semiconductor chip so as to change a position of the point bonding and decrease bonding force to the adhesive sheet by the adhesion. Then, the semiconductor chip is removed from the adhesive sheet.



(88) Date of publication of the international search report:
2 June 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.